

The first flip-up with autopilot arrived.

UNTIL TODAY:

THE SEMI-AUTOMATED WELDING MASK...

automatically darkens as soon as the welding arc ignites. The shade level must be set manually according to changing lighting.


optre/

like Flif autor

NEW:

THE FULLY AUTOMATED WELDING MASK...

automatically darkens as soon as the welding arc ignites. No manual shade level setting necessary. The optrel **liteflip** autopilot automatically adjusts to changing lighting.



optrel liteflip autopilot:


Combines the advantages of a flip-up welding helmet with the comfort of the optrel autopilot. Combines perfectly with the optrel e3000 respiratory protection.

Welding made easy.

Super lightweight flip-up welding helmet with automatic shade level adjustment makes welding much more comfortable and easy.

AUTOPILOT WITH SHADE LEVELS

With a shade level range from 5 to applications, can be handled without any manual adjustments at the helmet. And of course, without displacing the helmet itself. The welder is always protected perfectly.





TRUE-COLOR VIEW

The specially developed UV/IR filter allows a realistic perception of colours and at long last brings colour into the world of the welder.



TWILIGHT ADF TECHNOLOGY

Unlike other ADF lenses that rapidly return to light, the Twilight ADF Technology restores light more naturally, presenting a smoother transition to the eyes. This exclusive technology reduces eye fatigue on welders who are continuously welding, enabling them to work safer and more comfortably.



LIGHTWEIGHT

Weighing only 530g, the liteflip autopilot is one of the lightest flip-up welding helmets available. Its ergonomic design minimizes strain on the head and neck, ensuring comfort throughout the work day.



RESPIRATORY PROTECTION

The liteflip autopilot is perfectly combined with the optrel e3000 PAPR respiratory system. With its integrated high-performance particle filter (TH3), welders are adequately protected against smoke, dust, and aerosols.



2+1 YEAR WARRANTY

Register your optrel liteflip autopilot online and receive an additional year of warranty for free:

http://register.optrel.com



Helmet system	Item no.	Main accessories	Item no.
liteflip autopilot welding helmet	1006.700	optrel parking buddy	5002.900
liteflip autopilot welding helmet with industrial helmet	1006.750	Front cover lens	5000.391
liteflip autopilot fresh air helmet	4441.700	Safety lens	5000.390
liteflip autopilot fresh air helmet with industrial helmet	4441.750	optrel bag for helmets	8000.100





Desription	Fully automatic welding helmet (no manual adjustment necessary) with flip-up function for a clear view.			
	True-color view, ADF with shade level range 4/5-14M with autopilot (automatic shade level adjustment), +/- 2 individual manual offset, sensitivity adjustment, and opening delay with or without twilight function.			
Shade levels	Open / clear view:	shade level 1		
	Closed / inactive:	shade level 4		
	Closed / active:	shade levels 5-14		
Autopilot	Automatic shade level adjustment for shade level range 5 to 14 with individual calibration option of \pm 2.			
Power supply	Photovoltaic cell, 2 pcs batteries 3V exchangeable (CR2032)			
Operating time batteries	Approx. 3,000 hours (operating)		
Sensors	3 sensors			
Sensitivity	Infinite adjustment, ne "Super High" range	w with		
Switching time	Light to dark: 0.100 ms at room temp 0.100 ms at 55°C / 131°			
	Dark to light: 0.3 s or 1.5 s (with twili	ght function)		
Field of view	Flip-up open: 82 x 102	mm		
	Flip-up closed: 50 x 10	00 mm		

Classification	Optical class:	1	
EN379	Diffusion of light class:	1	
	Variations in luminous transmittance class:	1	
	Angle dependence of luminous transmittance class:	2	
Shape stability	Welding mask: up to 220°C / 428°F		
	Front cover lens: up to 137°C / 279°F		
Eye protection	Ultraviolet / Infrared Protection: maximum protection at any shade leve	el	
Operating temperature	-10°C to +70°C / 14°F to 158°F		
Storage temperature	e -20°C to +80°C / -4°F to 176°F		
Weight	Standard helmet: 530 g / 18.7 oz PAPR helmet: 730 g / 25.8 oz		
Application ranges	Any electric arc welding process Electrode Welding (Stick Welding, SMAW) / MIG / MAG (GMAW) / GMAW High melting rate process / Flux Core Wire Welding / TIG welding (GTAW) / Plasma Arc Welding / Plasmacutting & Oxy-gas Welding	d	
	Prohibited for laser welding!		
Scope of delivery	Welding helmet, instruction manual, storage bag, batteries, warranty card		
Standards	CE, ANSI Z87.1, EAC, complies with CS Z94.3	Α	
Warranty	2 years (except batteries)		
	1 year warranty extension for online product registration within the first 6 month. http://register.optrel.com		

